



ASK 2LD 48 V DC – 351329

Description

General Product Information	Insulating material	PA
	Insulating material	
	Inflammability class acc. to UL 94	V2
	Inflammability class acc. to UL 94	
	Packing Unit	25
	Packing Unit	
	Weight (g)	—
Dimensions	Weight (g)	
	Continuous Operating Temp.	(min.-max.)
	DIN-EN 45545Z	
	Width	8 mm
	Length	60 mm
TSE / CE Technical Data	Height (MR 32)	49 mm
	Height (MR 35x7.5)	45 mm
	Nominal Voltage	48V DC V ~
	Nominal Current	6.3 A
	Cross Section	6 mm ²
VDE Technical Data	Norm	EN 60947-7-3
	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	6.3 A
	Cross Section	AWG/26-8



ATEX Technical Data

Nominal Voltage — V ~
Nominal Current — A
Cross Section —

Connection Data

Minimum solid strand cross section 0.5 mm²
Maximum solid Strand cross section 10 mm²
Minimum fine Strand cross section 1.5 mm²
Maximum fine strand cross section 10 mm²
AWG Conductor Range 26-8
Connection Type screw/vidal?
Insulation Stripping length 12 mm
Tightening torque 0.8/1.2 Nm

48 VDC