



ASK 2LD GREY (220 VDC) – 351629

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	25
	Weight (g)	—
Dimensions	Width	8 mm
	Length	60 mm
	Height (MR 32)	49 mm
	Height (MR 35x7.5)	45 mm
TSE / CE Technical Data	Nominal Voltage	220V DC V ~
	Nominal Current	6.3 A
	Cross Section	6 mm ²
	Norm	EN 60947-7-3
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	6.3 A
	Cross Section	AWG/26-8
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	—
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	10 mm ²
	Minimum fine Strand cross section	1.5 mm ²



Maximum fine strand cross section	10 mm ²
AWG Conductor Range	26-8
Connection Type	screw/vidal?
Insulation Stripping length	12 mm
Tightening torque	0.8/1.2 Nm

220 VDC