



## ASK 2S GREY – 351109

### Description

<b>General Product Information</b>	Insulating material	PA
	Insulating material	
	Inflammability class acc. to UL 94	V2
	Inflammability class acc. to UL 94	
	Packing Unit	50
	Packing Unit	
	Weight (g)	—
	Weight (g)	
<b>Dimensions</b>	Continuous Operating Temp.	(min.-max.)
	DIN-EN 45545Z	
	Width	8 mm
	Length	60 mm
	Height (MR 32)	49 mm
<b>TSE / CE Technical Data</b>	Height (MR 35x7.5)	45 mm
	Nominal Voltage	500 V ~
	Nominal Current	6.3 A
	Cross Section	6 mm <sup>2</sup>
<b>VDE Technical Data</b>	Norm	EN 60947-7-3
	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm <sup>2</sup>
<b>UL / CSA Technical Data</b>	VDE Norm	—
	Nominal Voltage	300 V ~
	Nominal Current	6.3 A
<b>ATEX Technical Data</b>	Cross Section	AWG/26-8
	Nominal Voltage	— V ~

---

<b>Connection Data</b>	Nominal Current	— A
	Cross Section	—
	Minimum solid strand cross section	0.5 mm <sup>2</sup>
	Maximum solid Strand cross section	10 mm <sup>2</sup>
	Minimum fine Strand cross section	1.5 mm <sup>2</sup>
	Maximum fine strand cross section	10 mm <sup>2</sup>
	AWG Conductor Range	26-8
	Connection Type	screw/vidal?
	Insulation Stripping length	12 mm
Tightening torque	0.8/1.2 Nm	