



ASK 2S GREY – 351109

Description

General Product Information	Insulating material	PA
	Insulating material	
	Inflammability class acc. to UL 94	V2
	Inflammability class acc. to UL 94	
	Packing Unit	50
	Packing Unit	
	Weight (g)	—
	Weight (g)	
Dimensions	Continuous Operating Temp.	(min.-max.)
	DIN-EN 45545Z	
	Width	8 mm
	Length	60 mm
	Height (MR 32)	49 mm
TSE / CE Technical Data	Height (MR 35x7.5)	45 mm
	Nominal Voltage	500 V ~
	Nominal Current	6.3 A
	Cross Section	6 mm ²
VDE Technical Data	Norm	EN 60947-7-3
	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm ²
UL / CSA Technical Data	VDE Norm	—
	Nominal Voltage	300 V ~
	Nominal Current	6.3 A
ATEX Technical Data	Cross Section	AWG/26-8
	Nominal Voltage	— V ~

	Nominal Current	— A
	Cross Section	—
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	10 mm ²
	Minimum fine Strand cross section	1.5 mm ²
	Maximum fine strand cross section	10 mm ²
	AWG Conductor Range	26-8
	Connection Type	screw/vidal?
	Insulation Stripping length	12 mm
	Tightening torque	0.8/1.2 Nm