



ASK 3M GREY – 355109

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	30
	Weight (g)	—
Dimensions	Width	6 mm
	Length	53.5 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	72.5 mm
TSE / CE Technical Data	Nominal Voltage	500 V ~
	Nominal Current	10 A
	Cross Section	4 mm ²
	Norm	EN60947-7-3
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	600 V ~
	Nominal Current	10 A
	Cross Section	26-10
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	6 mm ²
	Minimum fine Strand cross section	0.5 mm ²
	Maximum fine strand cross section	6 mm ²



AWG Conductor Range	26-10
Connection Type	screw/vidal?
Insulation Stripping length	12 mm
Tightening torque	0.5/0.8 Nm