



## ASK 3M GREY – 355109

### Description

<b>General Product Information</b>	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	30
	Weight (g)	—
<b>Dimensions</b>	Width	6 mm
	Length	53.5 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	72.5 mm
<b>TSE / CE Technical Data</b>	Nominal Voltage	500 V ~
	Nominal Current	10 A
	Cross Section	4 mm <sup>2</sup>
	Norm	EN60947-7-3
<b>VDE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm <sup>2</sup>
	VDE Norm	—
<b>UL / CSA Technical Data</b>	Nominal Voltage	600 V ~
	Nominal Current	10 A
	Cross Section	26-10
<b>ATEX Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4
<b>Connection Data</b>	Minimum solid strand cross section	0.5 mm <sup>2</sup>
	Maximum solid Strand cross section	6 mm <sup>2</sup>
	Minimum fine Strand cross section	0.5 mm <sup>2</sup>
	Maximum fine strand cross section	6 mm <sup>2</sup>



AWG Conductor Range	26-10
Connection Type	screw/vidal?
Insulation Stripping length	12 mm
Tightening torque	0.5/0.8 Nm