



## ASK 4LD 24 VAC GREY – 351719

### Description

<b>General Product Information</b>	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	20
	Weight (g)	—
<b>Dimensions</b>	Width	10 mm
	Length	74.4 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	51.4 mm
<b>TSE / CE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	6.3 A
	Cross Section	6 mm <sup>2</sup>
	Norm	EN60947-7-3
<b>VDE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm <sup>2</sup>
	VDE Norm	—
<b>UL / CSA Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	A
	Cross Section	AWG/22-8
<b>ATEX Technical Data</b>	Nominal Voltage	V ~
	Nominal Current	A
	Cross Section	
<b>Connection Data</b>	Minimum solid strand cross section	0.5 mm <sup>2</sup>
	Maximum solid Strand cross section	10 mm <sup>2</sup>
	Minimum fine Strand cross section	1.5 mm <sup>2</sup>



Maximum fine strand cross section	6 mm <sup>2</sup>
AWG Conductor Range	22-8
Connection Type	screw/vidal?
Insulation Stripping length	12 mm
Tightening torque	0.5/0.8 Nm

24 VAC