



ASK 4LD 24 VDC GREY – 351729

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	20
	Weight (g)	—
Dimensions	Width	10 mm
	Length	74.4 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	51.4 mm
TSE / CE Technical Data	Nominal Voltage	— V ~
	Nominal Current	6.3 A
	Cross Section	6 mm ²
	Norm	EN60947-7-3
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	A
	Cross Section	AWG/22-8
ATEX Technical Data	Nominal Voltage	V ~
	Nominal Current	A
	Cross Section	
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	10 mm ²
	Minimum fine Strand cross section	1.5 mm ²



Maximum fine strand cross section	6 mm ²
AWG Conductor Range	22-8
Connection Type	screw/vidal?
Insulation Stripping length	12 mm
Tightening torque	0.5/0.8 Nm

24 VDC