



ASK 5LD 24V – 353429

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	50
	Weight (g)	—
Dimensions	Width	8 mm
	Length	58,50 mm
	Height (MR 32)	69,60 mm
	Height (MR 35x7.5)	51 mm
TSE / CE Technical Data	Nominal Voltage	— V ~
	Nominal Current	10 A
	Cross Section	4 mm ²
	Norm	EN 60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	10 A
	Cross Section	4 mm ²
	VDE Norm	EN 60947-7-2
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	10 A
	Cross Section	4
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	10 A
	Cross Section	4
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	6 mm ²
	Minimum fine Strand cross section	0.5 mm ²
	Maximum fine strand cross section	6 mm ²



AWG Conductor Range	26-10
Connection Type	screw/vidal?
Insulation Stripping length	9 mm
Tightening torque	0.5/1 Nm