



## AVK 25 BLUE – 304291

### Description

<b>General Product Information</b>	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	50
	Weight (g)	
<b>Dimensions</b>	Width	12 mm
	Length	52.80 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	58.70 mm
<b>TSE / CE Technical Data</b>	Nominal Voltage	750 V ~
	Nominal Current	101 A
	Cross Section	25 mm <sup>2</sup>
	Norm	EN 60947-7-1/N 60947-7-2
<b>VDE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	25 mm <sup>2</sup>
	VDE Norm	IEC 60947-7-1
<b>UL / CSA Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	25
<b>ATEX Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	25
<b>Connection Data</b>	Minimum solid strand cross section	1.5 mm <sup>2</sup>
	Maximum solid Strand cross section	35 mm <sup>2</sup>
	Minimum fine Strand cross section	1.5 mm <sup>2</sup>
	Maximum fine strand cross section	35 mm <sup>2</sup>



---

AWG Conductor Range	12-2
Connection Type	screw/vidal?
Insulation Stripping length	14 mm
Tightening torque	2.0/3.0 Nm