



AVK 25 GREY – 304290

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	50
	Weight (g)	
Dimensions	Width	12 mm
	Length	52.80 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	58.70 mm
TSE / CE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	101 A
	Cross Section	25 mm ²
	Norm	EN 60947-7-1/N 60947-7-2
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	25 mm ²
	VDE Norm	IEC 60947-7-1
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	25
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	25
Connection Data	Minimum solid strand cross section	1.5 mm ²
	Maximum solid Strand cross section	35 mm ²
	Minimum fine Strand cross section	1.5 mm ²
	Maximum fine strand cross section	35 mm ²



AWG Conductor Range	12-2
Connection Type	screw/vidal?
Insulation Stripping length	14 mm
Tightening torque	2.0/3.0 Nm