



## AVK 35T RD – 334210

### Description

<b>General Product Information</b>	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	40
	Weight (g)	—
	Continuous Operating Temp.	(min.-max.)
<b>Dimensions</b>	DIN-EN 45545Z	
	Width	16 mm
	Length	52.80 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	58.70 mm
<b>TSE / CE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	35 mm <sup>2</sup>
	Norm	EN 60947-7-2
<b>VDE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm <sup>2</sup>
	VDE Norm	IEC 60947-7-1/IEC60947-7-2
<b>UL / CSA Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	—
<b>Connection Data</b>	Minimum solid strand cross section	1.5 mm <sup>2</sup>
	Maximum solid Strand cross section	50 mm <sup>2</sup>
	Minimum fine Strand cross section	1.5 mm <sup>2</sup>
	Maximum fine strand cross section	35 mm <sup>2</sup>
	AWG Conductor Range	12-2



Connection Type  
Insulation Stripping length

screw/vidal?  
18 mm