



AVK 4 BLUE – 304131

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	100
	Weight (g)	
Dimensions	Width	6 mm
	Length	44.2 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	44.5 mm
TSE / CE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	32 A
	Cross Section	4 mm ²
	Norm	EN 60947-7-1
VDE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	32 A
	Cross Section	4 mm ²
	VDE Norm	IEC 60947-7-1
UL / CSA Technical Data	Nominal Voltage	600 V ~
	Nominal Current	30 A
	Cross Section	AWG/26-10
ATEX Technical Data	Nominal Voltage	400 V ~
	Nominal Current	28 A
	Cross Section	4
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	6 mm ²
	Minimum fine Strand cross section	1.5 mm ²
	Maximum fine strand cross section	4 mm ²



AWG Conductor Range	26-10
Connection Type	screw/vidal?
Insulation Stripping length	10 mm
Tightening torque	0.5 Nm