



AVK 95 – 304340

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	6
	Weight (g)	
Dimensions	Width	25 mm
	Length	80 mm
	Height (MR 32)	94.5 mm
	Height (MR 35x7.5)	97.5 mm
TSE / CE Technical Data	Nominal Voltage	1000 V ~
	Nominal Current	232 A
	Cross Section	95 mm ²
	Norm	EN 60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	95 mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	600 V ~
	Nominal Current	230 A
	Cross Section	AWG/2-4/0
ATEX Technical Data	Nominal Voltage	1000 V ~
	Nominal Current	217 A
	Cross Section	—
Connection Data	Minimum solid strand cross section	25 mm ²
	Maximum solid Strand cross section	95 mm ²
	Minimum fine Strand cross section	35 mm ²
	Maximum fine strand cross section	95 mm ²



AWG Conductor Range	2-4
Connection Type	screw/vidal?
Insulation Stripping length	25 mm
Tightening torque	6-10 Nm