



AYK 10/16-4 – 395100

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	20
	Weight (g)	—
Dimensions	Width	11 mm
	Length	70 mm
	Height (MR 32)	70.5 mm
	Height (MR 35x7.5)	65.5 mm
TSE / CE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	57/76 A
	Cross Section	10/16 mm ²
	Norm	EN 60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	16 mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	16
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	16
Connection Data	Minimum solid strand cross section	1.5 mm ²
	Maximum solid Strand cross section	16 mm ²
	Minimum fine Strand cross section	1.5 mm ²
	Maximum fine strand cross section	16 mm ²



AWG Conductor Range	16-8
Connection Type	screw/vidal?
Insulation Stripping length	12 mm
Tightening torque	1.2 Nm