



## PIK 2.5 ND-A GREY – 317219

### Description

<b>General Product Information</b>	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	20
	Weight (g)	—
<b>Dimensions</b>	Width	5 mm
	Length	64 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	61.3 mm
<b>TSE / CE Technical Data</b>	Nominal Voltage	500 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm <sup>2</sup>
	Norm	EN 60947-7-1
<b>VDE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm <sup>2</sup>
	VDE Norm	—
<b>UL / CSA Technical Data</b>	Nominal Voltage	300 V ~
	Nominal Current	20 A
	Cross Section	26-12
<b>ATEX Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	—
<b>Connection Data</b>	Minimum solid strand cross section	0.5 mm <sup>2</sup>
	Maximum solid Strand cross section	4 mm <sup>2</sup>
	Minimum fine Strand cross section	0.5 mm <sup>2</sup>



Maximum fine strand cross section	4 mm <sup>2</sup>
AWG Conductor Range	26-12
Connection Type	screw/vidal?
Insulation Stripping length	9 mm
Tightening torque	0.4 Nm

ONLY LOWER FLOORS is BRIDGEABLE