



PUK 2T GREY – 324209

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	20
	Weight (g)	—
Dimensions	Width	6 mm
	Length	71.70 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	53 mm
TSE / CE Technical Data	Nominal Voltage	440 V ~
	Nominal Current	24 A
	Cross Section	2,5 mm ²
	Norm	EN60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	— mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	300 V ~
	Nominal Current	24 A
	Cross Section	2.5
ATEX Technical Data	Nominal Voltage	400 V ~
	Nominal Current	24 A
	Cross Section	—
Connection Data	Minimum solid strand cross section	0,5 mm ²
	Maximum solid Strand cross section	4 mm ²
	Minimum fine Strand cross section	1,5 mm ²
	Maximum fine strand cross section	2,5 mm ²



AWG Conductor Range	24-12
Connection Type	screw/vidal?
Insulation Stripping length	8 mm
Tightening torque	0.4/0.6 Nm