



PUK 3S GREY – 324409

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	20
	Weight (g)	—
Dimensions	Width	6 mm
	Length	74.30 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	65.20 mm
TSE / CE Technical Data	Nominal Voltage	500 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm ²
	Norm	EN60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5 mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	4 mm ²
	Minimum fine Strand cross section	0.5 mm ²

Maximum fine strand cross section	2.5 mm ²
AWG Conductor Range	24-12
Connection Type	screw/vidal?
Insulation Stripping length	9 mm
Tightening torque	0.4 Nm

PUK 3 S terminal blocks minimize wiring time and costs and cabinet space when terminating three wire devices such as sensors, proximity switches etc.