



## YBK 10 BLUE – 306251

### Description

<b>General Product Information</b>	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	50
	Weight (g)	—
<b>Dimensions</b>	Width	10 mm
	Length	70 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	43 mm
<b>TSE / CE Technical Data</b>	Nominal Voltage	750 V ~
	Nominal Current	57 A
	Cross Section	10 mm <sup>2</sup>
	Norm	EN60947-7-1
<b>VDE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	10 mm <sup>2</sup>
	VDE Norm	—
<b>UL / CSA Technical Data</b>	Nominal Voltage	600 V ~
	Nominal Current	55 A
	Cross Section	AWG/20-6
<b>ATEX Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	10
<b>Connection Data</b>	Minimum solid strand cross section	0.5 mm <sup>2</sup>
	Maximum solid Strand cross section	16 mm <sup>2</sup>



Minimum fine Strand cross section	0.5 mm <sup>2</sup>
Maximum fine strand cross section	10 mm <sup>2</sup>
AWG Conductor Range	20-6
Connection Type	Yayl? ba?lant? / Spring connection
Insulation Stripping length	13 mm
Tightening torque	— Nm