



YBK 10 GREY – 306259

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	50
	Weight (g)	—
Dimensions	Width	10 mm
	Length	70 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	43 mm
TSE / CE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	57 A
	Cross Section	10 mm ²
	Norm	EN60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	10 mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	600 V ~
	Nominal Current	55 A
	Cross Section	AWG/20-6
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	10
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	16 mm ²



Minimum fine Strand cross section	0.5 mm ²
Maximum fine strand cross section	10 mm ²
AWG Conductor Range	20-6
Connection Type	Yayl? ba?lant? / Spring connection
Insulation Stripping length	13 mm
Tightening torque	— Nm