



YBK 2.5-2FT GREY – 324809

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	20
	Weight (g)	—
Dimensions	Width	5 mm
	Length	83.70 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	64.80 mm
TSE / CE Technical Data	Nominal Voltage	500 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm ²
	Norm	EN 60947-7-1/EN 60947-7-2
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5 mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	600 V ~
	Nominal Current	20 A
	Cross Section	AWG/22-12
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	4 mm ²
	Minimum fine Strand cross section	0.5 mm ²
	Maximum fine strand cross section	2.5 mm ²



AWG Conductor Range	22-12
Connection Type	spring/yayl?
Insulation Stripping length	10 mm
Tightening torque	— Nm