



## YBK 2.5E GREY – 326059

### Description

<b>General Product Information</b>	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	50
	Weight (g)	—
<b>Dimensions</b>	Width	5 mm
	Length	66.60 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	35.50 mm
<b>TSE / CE Technical Data</b>	Nominal Voltage	750 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm <sup>2</sup>
	Norm	EN 60947-7-1
<b>VDE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5 mm <sup>2</sup>
	VDE Norm	—
<b>UL / CSA Technical Data</b>	Nominal Voltage	600 V ~
	Nominal Current	20 A
	Cross Section	AWG/22-12
<b>ATEX Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5
<b>Connection Data</b>	Minimum solid strand cross section	0.5 mm <sup>2</sup>
	Maximum solid Strand cross section	4 mm <sup>2</sup>
	Minimum fine Strand cross section	0.5 mm <sup>2</sup>
	Maximum fine strand cross section	2.5 mm <sup>2</sup>



AWG Conductor Range	22-12
Connection Type	spring/yalyl?
Insulation Stripping length	10 mm