



## YBK 4-2F GREY – 318109

### Description

<b>General Product Information</b>	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	
	Weight (g)	—
<b>Dimensions</b>	Width	6 mm
	Length	90.3 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	55.5 mm
<b>TSE / CE Technical Data</b>	Nominal Voltage	750 V ~
	Nominal Current	32 A
	Cross Section	4 mm <sup>2</sup>
	Norm	EN 60947-7-1
<b>VDE Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4 mm <sup>2</sup>
	VDE Norm	—
<b>UL / CSA Technical Data</b>	Nominal Voltage	600 V ~
	Nominal Current	26 A
	Cross Section	22-10
<b>ATEX Technical Data</b>	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	—
<b>Connection Data</b>	Minimum solid strand cross section	0.5 mm <sup>2</sup>
	Maximum solid Strand cross section	6 mm <sup>2</sup>
	Minimum fine Strand cross section	0.5 mm <sup>2</sup>
	Maximum fine strand cross section	4 mm <sup>2</sup>



AWG Conductor Range	22-10
Connection Type	spring/yayl?
Insulation Stripping length	12 mm
Tightening torque	— Nm