



YBK 6 GREY – 306249

Description

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	100
	Weight (g)	—
Dimensions	Width	8 mm
	Length	64 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	38.5 mm
TSE / CE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	41 A
	Cross Section	6 mm ²
	Norm	EN60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	6 mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	600 V ~
	Nominal Current	35 A
	Cross Section	AWG/22-8
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	6
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	10 mm ²



Minimum fine Strand cross section	0.5 mm ²
Maximum fine strand cross section	6 mm ²
AWG Conductor Range	22-8
Connection Type	Yayl? ba?lant? / Spring connection
Insulation Stripping length	12 mm
Tightening torque	— Nm